

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 August 2005 (18.08.2005)

PCT

(10) International Publication Number
WO 2005/074813 A1

(51) International Patent Classification?: **A61B 17/00.**
17/12

(74) Agent: CLERC, Natalia; Isler & Pedrazzini AG, Gotthardstrasse 53, Postfach 6940, CH-8023 Zürich (CH).

(21) International Application Number:
PCT/CH2004/000059

(22) International Filing Date: 4 February 2004 (04.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): CARAG AG [CH/CH]; Bahnhofstrasse 9, CH-6340 Baar (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): THOMMEN, Daniel [CH/CH]; Industriestrasse 42, CH-6300 Zug (CH). FURRER, Simon [CH/CH]; Bundesstrasse 17, CH-6003 Luzern (CH). BERNHARD, Jérôme [CH/CH]; Zähringerstrasse 31, CH-8001 Zürich (CH). CHRISTEN, Lukas [CH/CH]; Stadthausstrasse 3, CH-6003 Luzern (CH). EGLI, Silvia [CH/CH]; Langhöfli, CH-6105 Schachen (CH). GUNDI, Franziska [CH/CH]; Dorfstrasse 33a, CH-6340 Baar (CH). ROBERT, Marc [CH/CH]; Hältikerstrasse 17, CH-6403 Küssnacht (CH). SUTER, Franz [CH/CH]; Blumenweg 12, CH-6340 Baar (CH).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AN IMPLANT FOR OCCLUDING A BODY PASSAGE



(57) Abstract: An implant for occluding a passage in a circulatory system of a human body comprises elongate members (1) which can be twisted into fixation structures and at least two occluding bodies (2, 2') being attached to the elongate members (1) and being arranged at a distance to each other. This implant combines the advantages of a single occluding body implant with the advantages of a double occluding body implant.

WO 2005/074813 A1

5

AN IMPLANT FOR OCCLUDING A BODY PASSAGE

10

FIELD OF THE INVENTION

The present invention generally relates to an implant for closing a passage in a circulatory system and more particular for closing a body passage of a human body, for example an aperture through the atrial septum or the ventricle septum of a heart or in a body channel.

15

BACKGROUND OF THE INVENTION

20 A well-working implant for occluding a passage in a circulatory system is disclosed in WO 02/38051. This implant has its particular application as a cardiological implant by means of which it is possible, for example, to close an aperture through the atrial septum or the ventricle septum of a heart. It is arranged to be deployed or built up (i.e., assembled) at a desired location in the body (e.g. the heart), in contrast to known other
25 implants (e.g. so-called umbrellas and sails) that are instead extended as soon as the compressed umbrella leaves its insertion sheath.

30

This implant includes a plurality of thin wire-like elongate members each having a proximal and a distal end and being made of non-bendable material. The implant further comprises two holders to which the ends of the elongate members are attached. By reducing the distance between the two holders the elongate members are caused to execute a twisting motion yielding in a plurality of radially extending loops. When the two holders are interlocked with each other, the loops are fixed in a fixation structure which

fixes the implant in the passage.

The implant further comprises an occluding body being fixed to the elongate members. This occluding body is deployed or expanded when the two holders are brought together and the passage is closed. In one embodiment, a balloon structure is expanded on both side of the passage, e.g. the atrial septum. In another preferred embodiment, a disk-shaped occluding body made of a flexible material is arranged in the middle between the two holders and hold in its expanded position by the twisted elongate members.

10 One of the advantages of using a single occluding body implant is that only one occluding body has to be opened and placed in the passage. However, sometimes, the opening in the passage is such, that the occluding body is not big enough to securely close the passage. It is then preferred to locate an occluding body on both sides of the septum each.

15 Such an implant is shown in US 5'171'259. It comprises a pair of patches each consisting of a resilient, foldable annular frame and a piece of cloth stretched over and fixed to the frame. The patches are so arranged as to face each other across a gap and sewed together concentrically with a thread slightly inwardly of the outer circumferential edge thereof in such a manner that as the thread is pulled the two patches are moved so as to approach each other. This implant is introduced into the passage using a catheter. First the first patch is released from the catheter and opened, then the catheter is retrieved a bit before the second patch is released and opened. US 4'836'204 discloses an implant comprising two balloons, wherein they are also opened one after the other. These im-
20 plants have the disadvantages, that two occluding bodies must be placed and opened in the passage at two different times during surgery.

US 6'117'159 shows a catheter delivered device to close a septal defect, the implant comprising a shaft with concentric parallel cuts through the wall of the device which
30 create flattened support struts. The centre of the support struts move radially away from the axis in a hinge like fashion in response to the movement of the device's proximal and distal ends toward the centre of the device. This device does not comprise an occluding body but it is coated with determinants which can improve tissue growth.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an improved implant for occluding a passage in a circulatory system, especially of a human body.

5

The foregoing object is achieved by means of an implant according to the features of claim 1.

The inventive implant comprises

- 10 a plurality of thin elongate members each having a first end and a second end;
a first holder to which the first ends of the elongate members are attached;
a second holder to which the second ends of the elongate members are attached, the
elongate members being attached to the first and second holders;
a first occluding body being attached to the elongate members;
15 the implant forming in a first state an elongated article extending along a longitudinal
axis, the implant being adapted in the first state for insertion into the circulatory system
and the implant being adapted to be brought into a second state in the circulatory system,
wherein the distance between the holders being reduceable in a manner to cause
the elongate members to execute a twisting motion relative to the axis to yield a plural-
20 ity of generally radially extending loops forming at least one fixation structure, thereby
increasing a cross-section of the occluding body and the at least one fixation structure
being fixable in the second state,
wherein
the implant comprises at least one second occluding body being attached to the elongate
25 members at a distance to the first occluding body and wherein the distance between the
first and the second occluding body is reduceable by reducing the distance between the
two holders, wherein at least one of the group of the following fixation structures is
formed: a first of said fixation structure between the first occluding body and the first
holder and a second of said fixation structure between the second occluding body and
30 the second holder.

Preferably, both fixations structures are built up when the holders are brought together.

- It was found, that this occluder comprising at least two occluding bodies can be opened in a better guided way into its second state. The elongate member are bended more willingly into their looped twisted fixation structure. The inventive occluder therefore demands less skill and experience to be introduced and located at the right place in the passage. Even when the lengths of the elongate members are chosen such that the first and the second occluding body do not open at the same time and/or the first and second fixation structure are not formed at the same time, they still are opened or formed respectively in the same movement, i.e. by bringing the two holders together.
- Since this implant comprises at least two occluding bodies, which can be built up on both sides of passage at the same time or with the same movement respectively, the advantages of the known double bodies occluder and the advantages of the single body occluder can be combined, without having the disadvantages thereof.
- These and other advantages and objects achieved by the present invention will be further appreciated and understood upon consideration of the following detailed description of preferred embodiments taken in conjunction with the drawings in which:

BRIEF DESCRIPTION OF THE DRAWINGS

- Figure 1 shows a perspective view of an implant according a first embodiment of the invention in an initial state;
- Figure 2 the implant according to figure 1 in a partly compressed state;
- Figure 3 the implant according to figure 1 in a first in-between state;
- Figure 4 the implant according to figure 1 in a second in-between state;
- Figure 5 the implant according to figure 1 in a third in-between state;
- Figure 6 the implant according to figure 1 in a second deployed state and

Figure 7 a perspective view of an implant according to the invention according to a second embodiment.

5

PREFERRED EMBODIMENTS

The device according to the invention is based on the implants disclosed in WO 02/38051, the disclosure thereof is incorporated in this description by reference.

10

The inventive device is employed as an implant for closing an internal passage, for example, an aperture in the atrial septum or the ventricle septum of a heart, or in another human or animal body channel which one wishes to close. The implant is compressible for insertion through a delivery mechanism, such as a body vein, and is deployable or
15 expansible for occluding the passage in the circulatory system when arrived at the position of the intended closing spot.

20

Figure 1 shows the implant of the present invention in an initial state, i.e., before the device is applied to the passage in a circulatory system, compressed during its insertion and deployed after it has arrived at the intended closing spot.

The implant comprises a plurality of thin elongate members 1, such as wires or threads, a first occluding body 2, at least one second occluding body 2', a first holder 3 and a second holder 4. The implant extends along a virtual longitudinal axis A.

25

The elongate members 1 are attached with their first, proximal ends to the first holder 3 and with their second distal ends to the second holder 4. Proximal means near to the surgeon, and distal near to the patient. The members 1 can be attached in a pre-twisted or un-twisted manner. The elongate members 1 are usually made of a thin stiff generally
30 inextensible, but somewhat flexible material. For example, they can be made of nitinol or another non-bendable material. Preferably they are made of Phynox, i.e. a cobalt-chromium-nickel alloy, or of a plastic. The figure shows eight elongate members 1. This is the preferred number, but it should be understood that the number of members can be

varied.

The first and second occluding bodies 2, 2' are located between the two holders 3, 4 and extend in a generally radial manner from the longitudinal axis A. They comprise a central hole 20, 20' each. In their circumferential region, the occluding bodies 2, 2' are attached to the elongate members 1. The bodies 2, 2' comprise outer holes 21, 21' through which the elongate members 1 extend. The elongate members 1 comprise thickened portions 10 arranged on both sides of the outer holes 21, 21' of the occluding bodies 2, 2' which serve to capture and mount the occluding bodies 2, 2', so that the position of the occluding bodies 2, 2' between pairs of two respective thickened portions 10 is fixed within spaces defined by pairs of said thickened portions 10.

The occluding bodies 2, 2' divide each of the elongate members 1 in three portions. A first portion 11 lays between the first holder 3 and the first occluding body 2, a second portion 12 between the second occluding body 2' and the second, distal holder 4 and the third portion 13 between the first and the second occluding body 2, 2'.

Preferably, at least the first and second portions 11, 12 of each elongate member 1 have approximately the same length. Preferably, also the third portions 13 have the same length. However, all of them can also have different lengths.

The occluding bodies 2, 2' are made of a flexible, for example fabric-like, material consistent with surgical use. A preferred material is Polyester. They can also be made of a biodegradable or bioabsorbable material. Preferably, both occluding bodies 2, 2' are made of the same material and have the same sizes. However, it is also possible to use different kinds of first and second occluding bodies.

The occluding bodies 2, 2' however should have a distal face 22 oriented toward the second holder 4 and a proximal face 23 oriented toward the first holder 3. They have at least in their deployed condition, preferably also in their initial position an at least approximately disk-shaped form, preferably a circular shape. Since they are made of flexible material, they can be compressed into a compressed form, for example being similar to an umbrella.

In order to introduce the implant into the passage, a carrier rod 5 and a driving implement 6, such as a catheter or another suitable sleeve, can be used. The implant can be inserted intravenously. However, it can also be introduced through the esophagus or other appropriate living body channels. The carrier rod 5 extends slidably moveable through the first holder 1 and the central holes 20, 20' in the first and second occluding body 2, 2' and is fixedly but removeably held in the second holder 4. Figure 2 shows the implant mounted on the rod 5 and being partly compressed by the sleeve 60 of the driving implement 6. Compressing the implant causes the occluding bodies 2, 2' to reduce their outer cross-section or diameter.

In a first totally compressed state the implant is introduced into the passage. When it is placed at the requested location, the sleeve 60 is pulled back. Second, a pushing rod 61 is used to push the first holder 3 towards the second holder 4, and/or the carrier rod 5 is pulled back thereby moving the second holder 4 closer to the first holder 3 which is in this case held in place. Because of the two holders 3, 4 approaching each other, the elongate members 1 are bended and finally twisted into fixation structures. The occluding bodies 2, 2' are at the same time deployed and regain their disk-shaped form.

Figures 3 to 5 show different in-between states of the implant during this movement. Moving the two holders 3, 4 together at first causes the first and second portions 11, 12 of the inextensible elongate members 1 to assume a gently outwardly bowed configuration each with respect to the longitudinal axis A. The third portions 13 are bent as well. Further moving the first holder 3 towards the second holder 4 causes the first and second portions 11, 12 of the elongate members 1 to assume a more bowed, almost semi-circular shape. At some stage, the non-bendable elongate members 1 pass through a critical point, whereupon the first and second portions 11, 12 snap into a generally radially-extending loops, yielding a somewhat concave petalshaped structure each. This means that the first and second portions 11, 12 finally twist and each portion 11, 12 form together with same portion of the other elongate members 1 a first and second fixation structure respectively. These fixation structures have a shape similar to a flower or a windwheel. The third portions 13 are bended less than the first and second portions 11, 12.

Preferably, the first and second portions 11, 12 are twisted in the same way and the first and second fixation structures obtained thereof have the same outer diameter. The third portion 13 is normally only bended like a spring, but not twisted like the first and second portions 11, 12. The third portion forms in this second state a bended structure which has preferably an outer diameter having approximately the same size than the diameter of the cross-section of the two occluding bodies 2, 2'. If the two occluding bodies 2, 2' have different sizes, the bended structure can have the same size as one of the occluding bodies 2, 2', wherein it can have the size of the smaller or the bigger one or a size in-between.

Figure 6 shows the implant in its final and second state. In this state, the implant is placed at the passage, the fixations structures are formed and the occluding bodies 2, 2' are deployed. The occluding bodies 2, 2' are stiffened and form a fluid tight closing body on both sides of the septum. The form of the occluding bodies 2, 2' can be the same as in the initial position or it can be expanded. Their location in the passage is fixed by the fixation structures formed by the twisted and fixed elongated members 1.

One way to keep the implant in this second state, i.e. to fix the elongate members 1 in their twisted position, is to attach the two holders 3, 4 to each other. In this embodiment, the two holders 3, 4 therefore comprise a locking mechanism, preferably consisting of snap together members 30, 40, lock the elongate members 1 in their twisted position. These locking means are already described in WO 02/38051 and its disclosure will therefore not be repeated here.

Figure 7 shows another preferred embodiment. This embodiment comprises a compressible body 7 made of a compressible material, such as a cotton swab. This body 7 is located between the two occluding bodies 2, 2' and held between the third portions 13 of the elongate members 1. This compressible material helps to occlude the passage.

The inventive implant combines the advantages of a single occluding body implant with the advantages of a double occluding body implant.

LIST OF REFERENCE NUMBERS

	1	elongate members
	10	thickened portion
5	11	first portion
	12	second portion
	13	third portion
	2	first occluding body
10	2'	second occluding body
	20	central holes
	20'	central holes
	21	outer holes
	21'	outer holes
15	22	distal face
	23	proximal face
	3	first holder
	30	first locking means
20		
	4	second holder
	40	second locking means
	5	carrier rod
25		
	6	driving implement
	60	sleeve
	61	pushing rod
30	7	compressible body
	A	longitudinal axis

CLAIMS

1. An implant for occluding a passage in a circulatory system, the implant comprising
5 a plurality of thin elongate members (1) each having a first end and a second end;
a first holder (3) to which the first ends of the elongate members (1) are attached;
a second holder (4) to which the second ends of the elongate members (1) are attached, the elongate members (1) being attached to the first and second holders (3, 4);
10 a first occluding body (2) being attached to the elongate members (1);
the implant forming in a first state an elongated article extending along a longitudinal axis (A), the implant being adapted in the first state for insertion into the circulatory system and the implant being adapted to be brought into a second state in the circulatory system, wherein the distance between the holders (3, 4) being reducible in a manner to cause the elongate members (1) to execute a twisting motion relative to the axis (A) to yield a plurality of generally radially extending loops forming at least one fixation structure, thereby increasing a cross-section of the occluding body (2) and the at least one fixation structure being fixable in the second state,
15 characterized in that
20 the implant comprises at least one second occluding body (2') being attached to the elongate members (1) at a distance to the first occluding body (2) and wherein the distance between the first and the second occluding body (2, 2') is reducible by reducing the distance between the two holders (3, 4), wherein at least one of
25 the group of the following fixation structures is formed: a first of said fixation structure between the first occluding body (2) and the first holder (3) and a second of said fixation structure between the second occluding body (2') and the second holder (4).
- 30 2. The implant according to claim 1, wherein both the first and the at least one second fixation structure are formed in the second state.
3. The implant according to one of claims 1 to 3, wherein there exists exactly one

- second occluding body (2, 2') and wherein the elongate members (1) have first portions (11) being arranged between the first holder (3) and the first occluding body (2), second portions (12) being arranged between the second holder (4) and the second occluding body (2') and third portions (13) being arranged between the first and second occluding body (2, 2').
- 5
4. The implant according to claim 3, wherein the first and second portions (11, 12) of each elongate member (1) have approximately the same length.
- 10
5. The implant according to claim 3, wherein the first, second and third portions (11, 12) of each elongate member (1) have approximately the same length.
6. The implant according to one of claims 3 or 4, wherein the third portions (13) are not twisted like the first and second portions (11, 12).
- 15
7. The implant according to one of claims 3 to 6, wherein in the second state the first portions (11) form the first fixation structure and the second portions (12) form the second fixation structure.
- 20
8. The implant according to one of claims 3 to 7, wherein in the second state the third portions form a bended structure with an outer diameter having approximately the same size as the diameter of the cross-section of at least one of the first or second occluding body (2, 2').
- 25
9. The implant according to one of claims 1 to 8, wherein in the second state the first and the at least one second occluding body (2, 2') have a cross-section having the same size.
- 30
10. The implant according to one of claims 1 to 9, wherein the first and the at least one second occluding body (2, 2') are made of a flexible material and each of said first and second occluding body (2, 2') has in the second state an approximately disk-shaped form and in the first state a compressed form.

11. The implant of claim 10, wherein the first and the at least second occluding body (2, 2') have an at least approximately circular shape.
12. The implant of one of claims 1 to 11, wherein the first and the at least one second occluding body (2, 2') comprise holes (20, 20') and wherein the elongate members (1) are extending through said holes (20, 20').
13. The implant according to one of claims 1 to 13, wherein all elongate members (1) have the same length.
14. The implant according to one of claims 1 to 13, wherein a compressible body (7) is arranged between the first and the at least one second occluding body (2, 2').




Fig. 1




Fig. 2




Fig. 3






Fig. 4

3/3



INTERNATIONAL SEARCH REPORT

International Application No.

PCT/CH2004/000059

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61B17/00 A61B17/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 02/38051 A (CARAG) 16 May 2002 (2002-05-16) cited in the application figures 12-14	1
A	EP 0 474 887 A (INOUE) 18 March 1992 (1992-03-18) figures 9,10,19,20	1
A	WO 01/49185 A (PFM) 12 July 2001 (2001-07-12) page 14, paragraph 4; figures 7,15b page 18, paragraph 4	1



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

7 October 2004

Date of mailing of the international search report

15/10/2004

Name and mailing address of the ISA

European Patent Office, F.B. 5816 Patentlaan 2
NL - 2280 HV Rijswijk
Tel: (+31-78) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-78) 340-3016

Authorized officer

Barton, S

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CH2004/000059

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 0238051 A	16-05-2002	AU 1202602 A	21-05-2002
		WO 0238051 A2	16-05-2002
		WO 2004047649 A1	10-06-2004
		CN 1486161 T	31-03-2004
		EP 1331885 A2	06-08-2003
		JP 2004512153 T	22-04-2004
		US 2003149463 A1	07-08-2003
EP 0474887 A	18-03-1992	JP 1847578 C	07-06-1994
		JP 3286752 A	17-12-1991
		JP 5060933 B	03-09-1993
		JP 1847579 C	07-06-1994
		JP 3286753 A	17-12-1991
		JP 5060934 B	03-09-1993
		AT 107150 T	15-07-1994
		CA 2057018 A1	03-10-1991
		DE 69102515 D1	21-07-1994
		DE 69102515 T2	20-10-1994
		EP 0474887 A1	18-03-1992
		WO 9115155 A1	17-10-1991
		US 5171259 A	15-12-1992
WO 0149185 A	12-07-2001	DE 10000137 A1	12-07-2001
		AU 2512901 A	16-07-2001
		WO 0149185 A1	12-07-2001
		EP 1246570 A1	09-10-2002
		US 2003171774 A1	11-09-2003